Bixolon SLP-DX220

Bixolon SLP-DX220 label printer Direct thermal 203 x 203 DPI 152 mm/sec Wired Wi-Fi



PRINT TECHNOLOGY
Direct thermal

RESOLUTION
203 x 203 DPI

PRINT SPEED
152 mm/sec

MAX PRINT WIDTH
5.4 cm

CONNECTIVITY
USB, Wi-Fi

PRINTER LANGUAGES
BPL

OVERVIEW

203 dpi, 6 ips, 64 MB SDRAM, 128 MB FlashROM, USB, Serial, Dark Grey

TECHNICAL SPECIFICATIONS

Print quality

Maximum resolution	203 x 203 DPI
Maximum printing width	5.4 cm

Printing

Minimum print length	6 mm
Colour	No
Printing colours	Black
Print speed	152 mm/sec
Print technology	Direct thermal
Maximum print length	2 m

Design

Navigation key	Yes
LED indicators	Yes
Product colour	Black

Network

Wi-Fi	Yes

Memory

Internal memory	64 MB
Flash memory	128 MB

Paper handling

Supported paper width	15 - 60 mm
Media thickness	0.06 - 0.2 mm
Maximum roll diameter	13 cm

Ports & interfaces

USB 2.0 ports quantity	1
RS-232 ports	1
Connectivity technology	Wired
USB port	Yes

Performance

Built-in barcodes	1D, 2D, AZTECCODE, CODABAR (NW-7), Code 11, Code 39, Code 93, Code-128 Codabar Library, Data Matrix, EAN13, EAN8, GS1 DataBar, IMB, Industrial 2/5, Interleaved 2/5, MicroPDF417, PDF417, POSTNET, QR Code, TLC39, UPC-A, UPC-E
Page description languages	BPL

Power

AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz

Technical details

Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.

Sustainability certificates	ENERGY STAR

Operational conditions

Storage temperature (T-T)	10 - 90 °C
Storage relative humidity (H-H)	-20 - 60%
Operating temperature (T-T)	10 - 80 °C
Operating relative humidity (H-H)	0 - 40%

Weight & dimensions

Width	120 mm
Depth	230 mm
Height	170 mm
Weight	1.36 kg

Order or get advice
Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434
website@barcodegenie.co.uk
Scan to view this product online.

Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.