Bixolon SPP-L410 203 x 203 DPI Direct thermal

Bixolon SPP-L410 203 x 203 DPI Direct thermal Mobile printer



PRINT TECHNOLOGY
Direct thermal

RESOLUTION
203 x 203 DPI

MAX PRINT WIDTH
10.4 cm

CONNECTIVITY
USB, Ethernet, Wi-Fi

PRINTER LANGUAGES
BPL, CPCL-native, SLCS, ZPL II

OVERVIEW

Direct Thermal, 203 dpi, 104 mm, 0.07 - 0.15 mm, IP54, Black

TECHNICAL SPECIFICATIONS

Printing

Colour	No
Type	Mobile printer
Print technology	Direct thermal
Maximum resolution	203 x 203 DPI

Performance

Built-in barcodes	1D, Codablock, Code 11, Code 128 (A/B/C), Code 39, Code 49, Code 93, Data Matrix, EAN13, EAN8, GS1 Databar (RSS-14), Industrial 2/5, Interleaved 2/5, LOGMARS, MSI, MaxiCode, MicroPDF417, PDF417, POSTNET, Plessey, QR Code, Standard 2/5, TLC39, UPC-A, UPC-E

Paper handling

Maximum media length	11.2 cm
Printing media thickness	7 µm
Maximum roll diameter	5.6 cm
Maximum printing width	10.4 cm

Ports & interfaces

USB port	Yes
Serial interface	Yes

Network

Ethernet LAN	Yes
Wi-Fi	Yes

Technical details

International Protection (IP) code	IP54
Product colour	Black
Sustainability certificates	ENERGY STAR

Features

Internal memory	128 MB
Flash memory	256 MB
Page description languages	BPL, CPCL-native, SLCS, ZPL II
Storage media	Flash

Power

Power source type	Battery
Battery voltage	7.3 V
Battery capacity	2850 mAh

Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.

Operational conditions

Storage temperature (T-T)	-30 - 70 °C
Operating temperature (T-T)	-15 - 50 °C
Operating relative humidity (H-H)	10 - 80%

Weight & dimensions

Width	143 mm
Depth	138 mm
Height	66 mm
Weight	530 g

Order or get advice
Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434
website@barcodegenie.co.uk
Scan to view this product online.

Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.