

# Bixolon XD3-40

Bixolon XD3-40 label printer Direct thermal / Thermal transfer 203 x 203 DPI 127 mm/sec Wireless Wi-Fi



PRINT TECHNOLOGY

**Direct thermal / Thermal transfer**

RESOLUTION

**203 x 203 DPI**

PRINT SPEED

**5 lpm**

MAX PRINT WIDTH

**10.4 cm**

MAX LABEL WIDTH

**11.8 cm**

CONNECTIVITY

**USB, Wi-Fi**

PRINTER LANGUAGES

**BPL, SLCS**

## OVERVIEW

Thermal Transfer Desktop Label Printer, Up to 5 ips (127 mm/sec), 203 dpi, 64 MB SDRAM, 128 MB Flash

## TECHNICAL SPECIFICATIONS

### Print quality

|                        |               |
|------------------------|---------------|
| Maximum resolution     | 203 x 203 DPI |
| Maximum printing width | 10.4 cm       |
| Maximum print height   | 100 cm        |

### Printing

|                       |                                   |
|-----------------------|-----------------------------------|
| Print speed           | 5 lpm                             |
| Print technology      | Direct thermal / Thermal transfer |
| Margin depth settings | Fixed                             |

### Network

|       |     |
|-------|-----|
| Wi-Fi | Yes |
|-------|-----|

### Memory

|                 |        |
|-----------------|--------|
| Internal memory | 64 MB  |
| Flash memory    | 128 MB |

### Paper handling

|                       |               |
|-----------------------|---------------|
| Ribbon width          | 11 cm         |
| Ribbon length         | 300 m         |
| Media thickness       | 0.06 - 0.2 mm |
| Maximum roll diameter | 12.7 cm       |

|                     |         |
|---------------------|---------|
| Maximum label width | 11.8 cm |
|---------------------|---------|

### Ports & interfaces

|                         |          |
|-------------------------|----------|
| Connectivity technology | Wireless |
| USB port                | Yes      |

### Performance

|                            |           |
|----------------------------|-----------|
| Page description languages | BPL, SLCS |
|----------------------------|-----------|

### Design

|                  |       |
|------------------|-------|
| Product colour   | Black |
| Built-in display | No    |

### Power

|                    |             |
|--------------------|-------------|
| AC input voltage   | 100 - 240 V |
| AC input frequency | 50 - 60 Hz  |

### Technical details

|                                     |     |
|-------------------------------------|-----|
| Windows operating systems supported | Yes |
| Mac operating systems supported     | Yes |

### System requirements

Linux operating systems supported    Yes

Operating relative humidity (H-H)    10 - 80%

**Operational conditions**

**Weight & dimensions**

Storage temperature (T-T)    -20 - 60 °C

Width    210 mm

Storage relative humidity (H-H)    10 - 90%

Depth    284 mm

Operating temperature (T-T)    5 - 40 °C

Height    186 mm

Weight    2.6 kg

**Order or get advice**

Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

**0113 487 7434**

[website@barcodegenie.co.uk](mailto:website@barcodegenie.co.uk)

Scan to view this product online.

