Brother TD-2125NWB

Brother TD-2125NWB label printer Direct thermal 203 x 203 DPI 152.4 mm/sec Wired Ethernet LAN Wi-Fi Bluetooth



PRINT TECHNOLOGY
Direct thermal

RESOLUTION
203 x 203 DPI

PRINT SPEED
152.4 mm/sec

MAX PRINT WIDTH
5.6 cm

MAX LABEL WIDTH
6.3 cm

CONNECTIVITY
USB, Ethernet, Wi-Fi, Bluetooth

PRINTER LANGUAGES
CPCL-native, ESC P

OVERVIEW

Versatile, compact desktop label printer with a built-in network, wireless and bluetooth connectivity. Print professional quality custom labels, wristbands and receipts up to 63mm in width at 152mm/sec.

KEY FEATURES

- High quality 203dpi print resolution
- Network capability / USB, serial, WiFi and bluetooth connectivity
- Free 3 year return to base warranty. Advanced exchange service up to five years available to purchase.
- Print from a PC or mobile device, or add on optional touch panel display (PA-TDU-001) for stand-alone printing.
- ZPL II printer language emulation

TECHNICAL SPECIFICATIONS

Print quality

Maximum resolution	203 x 203 DPI
Maximum printing width	5.6 cm

Printing

Colour	No
Print speed	152.4 mm/sec
Print technology	Direct thermal
Maximum print length	1 m

Display

Display	No

Network

Wi-Fi	Yes
Ethernet LAN	Yes

Memory

Internal memory	256 MB
Flash memory	64 MB

Paper handling

Maximum roll diameter	12.7 cm
Maximum label width	6.3 cm

Ports & interfaces

Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Bluetooth profiles	HCRP, OPP, SSP
USB 2.0 ports quantity	1
RS-232 ports	1

Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.

Connectivity technology	Wired
Bluetooth version	5.2
Bluetooth	Yes
USB port	Yes

Performance

Mobile operating systems supported	Android 10, Android 10.0, Android 11.0, Android 12.0, Android 5.0, Android 5.1, Android 6.0, Android 7.0, Android 7.1, Android 7.1.2, Android 8.0, Android 8.1, Android 9.0, iOS 10.0, iOS 11.0, iOS 11.4, iOS 12, iOS 13, iOS 13.4, iOS 14, iOS 14.5, iOS 15, iOS 9.0, iOS 9.1, iOS 9.2, iOS 9.3
Languages support	Multi
Number of languages	11
Built-in barcodes	CODABAR (NW-7), Code 39, Code-128 Codabar Library, Data Matrix, EAN13, EAN8, GS1 DataBar, GS1 DataBar Expanded, GS1 DataBar Expanded Stacked, GS1 DataBar Limited, GS1 DataBar Omnidirectional, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Truncated, ITF, MaxiCode, PDF417, POSTNET, QR Code, UPC-A, UPC-E
Security algorithms	64-bit WEP, 128-bit WEP, EAP-FAST, EAP-PEAP, EAP-TLS, EAP-TTLS, SNMPv3, SSL/TLS, WPA-PSK, WPA2-PSK, WPA3-EAP
Page description languages	CPCL-native, ESC P

Design

Product colour	Black, White
Built-in display	No

Power

External power adapter	Yes

Technical details

Server operating systems supported	Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019, Windows Server 2022
Windows operating systems supported	Windows 10, Windows 11, Windows 8, Windows 8.1
Networking features	10/100BASE-TX
Country of origin	China

Weight & dimensions

Width	180 mm
Depth	284 mm
Height	265 mm
Weight	2.12 kg
Package weight	2.83 kg

Packaging content

Manual	Yes
AC adapter included	Yes
Quick start guide	Yes
Cables included	USB

Order or get advice
Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434
website@barcodegenie.co.uk
Scan to view this product online.

Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.