

Citizen CL-E730

Citizen CL-E730 label printer Direct thermal / Thermal transfer 300 x 300 DPI 150 mm/sec Wired Ethernet LAN



PRINT TECHNOLOGY

Direct thermal / Thermal transfer

RESOLUTION

300 x 300 DPI

PRINT SPEED

150 mm/sec

MAX PRINT WIDTH

10.4 cm

CONNECTIVITY

USB, Ethernet

OVERVIEW

300 dpi, 150 mm/s, 12.5-118 mm, USB 2.0, RJ-45, 16 MB, 32 MB SDRAM, 250x458x261 mm

TECHNICAL SPECIFICATIONS

Print quality

Maximum resolution	300 x 300 DPI
Maximum printing width	10.4 cm

Printing

Colour	No
Print speed	150 mm/sec
Print technology	Direct thermal / Thermal transfer

Design

LED indicators	Status
Backlight display	Yes
Display	LCD
Product colour	Black

Network

Wi-Fi	No
Ethernet LAN	Yes

Memory

Internal memory	32 MB
Flash memory	16 MB

Paper handling

Supported paper width	12.5 - 118 mm
Media thickness	0.0635 - 0.254 mm

Maximum roll diameter	20 cm
Maximum media length	4.01 m
Core diameter	7.5 cm

Ports & interfaces

USB 2.0 ports quantity	1
Optional connectivity	Parallel, Serial (RS-232), Wireless LAN
Connectivity technology	Wired
USB port	Yes

Power

Power consumption (standby)	2.9 W
Power consumption (printing)	72 W
AC input voltage	100 - 230 V

Technical details

Server operating systems supported	Windows Server 2008 R2, Windows Server 2012
Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows 8.1
Sustainability certificates	ENERGY STAR

System requirements

Linux operating systems supported	Yes
-----------------------------------	-----

Weight & dimensions		Height	261 mm
Width	250 mm	Weight	11 kg
Depth	458 mm		

Order or get advice

Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434

website@barcodegenie.co.uk

Scan to view this product online.

