

Citizen CT-S310II Wired Thermal

Citizen CT-S310II Wired Thermal POS printer



PRINT TECHNOLOGY

Thermal

PRINT SPEED

160 mm/sec

CONNECTIVITY

USB

OVERVIEW

CT-S310II - 8 dots/mm(203 dpi), 58/80 mm, 160mm/s, 384 Kb, RS232, USB, 32 W, 1.8kg

TECHNICAL SPECIFICATIONS

Printing

Type	POS printer
Print technology	Thermal
Print speed	160 mm/sec
Character size	1.5 x 3 mm

Performance

Built-in barcodes	Code 128 (A/B/C), Code 39, EAN13, EAN8, ITF-14, PDF417, QR Code, UPC-A, UPC-E
-------------------	---

Paper handling

Supported paper width	80, 58 mm
Printing media thickness	65 - 75 µm
Maximum roll diameter	8.3 cm

Ports & interfaces

Standard interfaces	USB 2.0, Serial
Connectivity technology	Wired
USB 2.0 ports quantity	1
Serial ports quantity	1
USB port	Yes
Serial interface	Yes

Network

Ethernet LAN	No
Wi-Fi	No

Print technology

Column capacity	58mm: 52/46, 80mm:72/64
-----------------	-------------------------

Technical details

Product colour	Black
Buffer size	4 KB
Autocutter durability	2 million cuts

Features

Certification	UL, C-UL, FCC, TÜV, CE, CCC
---------------	-----------------------------

Power

AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power consumption (printing)	32 W

Operational conditions

Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	5 - 45 °C

Operating relative humidity (H-H)	10 - 90%	Weight	1.8 kg
		Dimensions (WxDxH)	140 x 195 x 132 mm

Weight & dimensions

Order or get advice

Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434

website@barcodegenie.co.uk

Scan to view this product online.

