

Citizen CT-S801II 203 x 203 DPI Direct thermal

Citizen CT-S801II 203 x 203 DPI Direct thermal POS printer



PRINT TECHNOLOGY
Direct thermal

RESOLUTION
203 x 203 DPI

PRINT SPEED
300 mm/sec

OVERVIEW

CT-S801II, 203 dpi, 300 mm/s, 80/83 mm, label, 145x192x148 mm

KEY FEATURES

- High contrast LCD display
- Full range of interface options incl. Bluetooth (Apple and Android compatible)
- Integrated power supply
- Choice of paper widths

TECHNICAL SPECIFICATIONS

Printing

Character sets	Katakana, PC437, PC850, PC858, PC860, PC863, PC865, Thai code 18, WPC1252
Type	POS printer
Print technology	Direct thermal
Print speed	300 mm/sec
Maximum resolution	203 x 203 DPI
Character size	1.5 x 3 mm

Performance

Built-in barcodes	CODABAR (NW-7), Code 128 (A/B/C), Code 39, Code 93, PDF417, QR Code, UPC-A, UPC-E
-------------------	---

Paper handling

Supported paper width	80/83 mm
Printing media thickness	65-75/75-150 µm

Maximum roll diameter	8.3 cm
-----------------------	--------

Network

Ethernet LAN	No
Wi-Fi	No

Technical details

Windows operating systems supported	Windows 2000, Windows Vista, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Ribbon life	200 million characters
Product colour	Black
Buffer size	4 KB
Autocutter durability	2 million cuts
Cutter	Yes
Sustainability certificates	ENERGY STAR

Features

Flash memory	0.384 MB
Certification	UL, C-UL, FCC A, TUV-Bauart, CE

Design

Built-in display	Yes
------------------	-----

Power

AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power source type	DC
Power consumption (printing)	45 W

Operational conditions

Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	5 - 45 °C
Operating relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	145 mm
Depth	192 mm
Height	148 mm
Weight	2 kg

Order or get advice

Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434

website@barcodegenie.co.uk

Scan to view this product online.

