Epson TM-U295 (272)

Epson TM-U295 (272): Serial, w/o PS, ECW



CONNECTIVITY
Wired

OVERVIEW

TM-U295 Slip Printer/ White/ RS-232C

TECHNICAL SPECIFICATIONS

Printing

Colour	No
Character density	16.2 cpi

Paper handling

Printing media thickness	0.09/0.35 µm

Ports & interfaces

Interface	RS-232, Drawer kick-out
Connectivity technology	Wired

Technical details

Ribbon life	1.5 million characters
Product colour	White
Country of origin	Japan
Box contents	Main unit, Ribbon, User manual

Features

Safety	UL, CSA C22.2 No. 950
Mean time between failures (MTBF)	180000 h
Sound pressure level (printing)	65 dB
Maximum number of copies	2 copies

Operational conditions

Storage temperature (T-T)	-10 - 50 °C
Storage relative humidity (H-H)	30 - 90%
Operating temperature (T-T)	5 - 40 °C
Operating relative humidity (H-H)	30 - 85%

Certificates

Electromagnetic compatibility	VCCI class A, FCC class A, CE marking

Weight & dimensions

Width	180 mm
Depth	191 mm
Height	102 mm
Package width	235 mm
Package depth	270 mm
Package height	185 mm
Package weight	1.84 kg
Weight	1.6 kg
Dimensions (WxDxH)	180 x 190.5 x 101.5 mm

Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.

Order or get advice
Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434
website@barcodegenie.co.uk
Scan to view this product online.

Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.