

Honeywell PC41E-D

Honeywell PC41E-D label printer Direct thermal / Thermal transfer 300 x 300 DPI 100 mm/sec Wired & Wireless Ethernet LAN Wi-Fi Bluetooth



PRINT TECHNOLOGY

Direct thermal / Thermal transfer

RESOLUTION

300 x 300 DPI

PRINT SPEED

100 mm/sec

MAX PRINT WIDTH

10.8 cm

MAX LABEL WIDTH

11.4 cm

CONNECTIVITY

USB, Ethernet, Wi-Fi, Bluetooth

PRINTER LANGUAGES

DP, DPL, EPL, XML, ZPL II

OVERVIEW

300 dpi (12 dots/mm), USB, LAN, 1D/2D, 128MB SDRAM/128 MB Flash, Wi-Fi 5, IEEE 802.11 a/b/g/n/ac, No Power Cord

TECHNICAL SPECIFICATIONS

Print quality

Maximum resolution	300 x 300 DPI
Maximum printing width	10.8 cm
Maximum print height	4.83 m

Printing

Colour	No
Print speed	100 mm/sec
Print technology	Direct thermal / Thermal transfer

Display

Display	LED
---------	-----

Network

Wi-Fi	Yes
Ethernet LAN	Yes

Memory

Internal memory	128 MB
Flash memory	128 MB

Paper handling

Ribbon width	11 cm
Ribbon length	300 m
Maximum roll diameter	12.7 cm
Maximum label width	11.4 cm
Core diameter	3.81 cm

Ports & interfaces

Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n)
Connectivity technology	Wired & Wireless
Bluetooth version	5.0
Bluetooth	Yes
USB port	Yes

Performance

Built-in barcodes	1D, 2D, AZTECCODE, Code 49, Data Matrix, EAN13, EAN8, MSI, MaxiCode, MicroPDF417, PDF417, Planet, POSTNET, Plessey, QR Code
Image formats supported	BMP, GIF, PCX, PNG

Certification	CE, C TUV US, FCC, IC, CB, EN 62368-1, IEC 62368-1, EMC
---------------	---

Page description languages	DP, DPL, EPL, XML, ZPL II
----------------------------	---------------------------

Design

Product colour	Black
Control type	Buttons
Built-in display	Yes

Power

AC adapter output voltage	24 V
AC adapter output current	2.5 A
AC input voltage	90 - 264 V
Power source type	AC

Technical details

Supported network protocols	TCP/IP (TCP, UDP, M, IGMP), LPR/ LPD, Telnet/SSH, FTP/SFTP, BOOTP, DHCP, HTTP/HTTPS, SMTP IPv4/IPv6
-----------------------------	---

Operational conditions

Storage temperature (T-T)	-40 - 60 °C
Storage relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	5 - 40 °C
Operating relative humidity (H-H)	10 - 80%

Weight & dimensions

Width	184 mm
Depth	222 mm
Height	174 mm
Weight	1.5 kg

Order or get advice

Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434

website@barcodegenie.co.uk

Scan to view this product online.

