

Honeywell PC42E-T

Honeywell PC42E-T label printer Direct thermal / Thermal transfer 300 x 300 DPI 100 mm/sec Wired Ethernet LAN Wi-Fi Bluetooth



PRINT TECHNOLOGY

Direct thermal / Thermal transfer

RESOLUTION

300 x 300 DPI

PRINT SPEED

6 lpm

MAX PRINT WIDTH

10.8 cm

CONNECTIVITY

USB, Ethernet, Wi-Fi, Bluetooth

OVERVIEW

Desktop Thermal Transfer Barcode Printer

TECHNICAL SPECIFICATIONS

Print quality

Maximum resolution	300 x 300 DPI
Maximum printing width	10.8 cm
Maximum print height	4.83 m

Printing

Minimum print length	9.6 mm
Colour	No
Print speed	6 lpm
Print technology	Direct thermal / Thermal transfer

Display

Display	LED
---------	-----

Network

Wi-Fi	Yes
Ethernet LAN	Yes

Memory

Internal memory	128 MB
Flash memory	128 MB

Paper handling

Ribbon width	11 cm
Ribbon length	300 m

Ports & interfaces

Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
USB 2.0 ports quantity	1
Connectivity technology	Wired
Bluetooth version	5.0
Bluetooth	Yes
USB port	Yes

Performance

Built-in barcodes	1D, 2D, AZTECCODE, Code 49, Data Matrix, EAN13, EAN8, MSI, MaxiCode, MicroPDF417, PDF417, Planet, POSTNET, Plessey, QR Code
-------------------	---

Design

Product colour	Black
On Screen Display (OSD) languages	German, English, Spanish, Italian, Thai, Japanese, Portuguese, Simplified Chinese, Korean, Russian, Traditional Chinese, French

Built-in display Yes

Power

AC input voltage 90 - 264 V

Operational conditions

Storage temperature (T-T) -40 - 60 °C

Storage relative humidity (H-H) 10 - 90%

Operating temperature (T-T) 5 - 40 °C

Operating relative humidity (H-H) 10 - 80%

Weight & dimensions

Width 198 mm

Depth 273 mm

Height 169 mm

Weight 2.04 kg

Order or get advice

Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434

website@barcodegenie.co.uk

Scan to view this product online.

