

Honeywell PC42E-T

Honeywell PC42E-T label printer Direct thermal / Thermal transfer 203 x 203 DPI 100 mm/sec Wired Ethernet LAN



PRINT TECHNOLOGY

Direct thermal / Thermal transfer

RESOLUTION

203 x 203 DPI

PRINT SPEED

100 mm/sec

MAX PRINT WIDTH

10.8 cm

MAX LABEL WIDTH

11.4 cm

CONNECTIVITY

USB, Ethernet

PRINTER LANGUAGES

DP, DPL, EPL, XML, ZPL II

OVERVIEW

Direct thermal / Thermal transfer, 203 dpi (8 dots/mm), 100 mm/s, 108 mm, USB, LAN, 1D/2D

TECHNICAL SPECIFICATIONS

Print quality

Maximum resolution	203 x 203 DPI
Maximum printing width	10.8 cm
Maximum print height	4.83 m

Printing

Colour	No
Print speed	100 mm/sec
Print technology	Direct thermal / Thermal transfer

Display

Display	LED
---------	-----

Network

Wi-Fi	No
Ethernet LAN	Yes

Memory

Internal memory	128 MB
-----------------	--------

Paper handling

Ribbon width	11 cm
--------------	-------

Ribbon length	300 m
Maximum roll diameter	12.7 cm
Maximum label width	11.4 cm
Core diameter	3.81 cm

Ports & interfaces

Connectivity technology	Wired
USB port	Yes

Performance

Built-in barcodes	1D, 2D, AZTECCODE, Code 49, Data Matrix, EAN13, EAN8, MSI, MaxiCode, MicroPDF417, PDF417, Planet, POSTNET, Plessey, QR Code
Image formats supported	BMP, GIF, PCX, PNG
Certification	CE, C TUV US, FCC, IC, CB, EN 62368-1, IEC 62368-1, EMC
Page description languages	DP, DPL, EPL, XML, ZPL II

Design

Product colour	Black, White
Control type	Buttons

Built-in display	Yes
------------------	-----

Power

AC adapter output voltage	24 V
---------------------------	------

AC adapter output current	2.5 A
---------------------------	-------

AC input voltage	90 - 264 V
------------------	------------

Power source type	AC
-------------------	----

Technical details

Supported network protocols	TCP/IP (TCP, UDP, M, IGMP), LPR/ LPD, Telnet/SSH, FTP/SFTP, BOOTP, DHCP, HTTP/HTTPS, SMTP IPv4/IPv6
-----------------------------	--

Operational conditions

Storage temperature (T-T)	-40 - 60 °C
---------------------------	-------------

Storage relative humidity (H-H)	10 - 90%
---------------------------------	----------

Operating temperature (T-T)	5 - 40 °C
-----------------------------	-----------

Operating relative humidity (H-H)	10 - 80%
-----------------------------------	----------

Weight & dimensions

Width	198 mm
-------	--------

Depth	273 mm
-------	--------

Height	168 mm
--------	--------

Weight	2.04 kg
--------	---------

Order or get advice

Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434

website@barcodegenie.co.uk

Scan to view this product online.

