

Honeywell PM45 Compact

Honeywell PM45 Compact label printer Thermal transfer 203 x 203 DPI 350 mm/sec Wired Ethernet LAN



PRINT TECHNOLOGY

Thermal transfer

RESOLUTION

203 x 203 DPI

PRINT SPEED

350 mm/sec

MAX PRINT WIDTH

10.8 cm

MAX LABEL WIDTH

11.4 cm

CONNECTIVITY

USB, Ethernet

PRINTER LANGUAGES

DP, DPL, IPL, XML, ZPL II

OVERVIEW

PM45 Compact, Full Touch Display, Ethernet, Fixed Hanger, Thermal Transfer, 203 DPI, Power Cord Not Included

TECHNICAL SPECIFICATIONS

Print quality

Maximum resolution	203 x 203 DPI
Maximum printing width	10.8 cm

Printing

Colour	No
Printing colours	Black
Print speed	350 mm/sec
Print technology	Thermal transfer
Maximum print length	4.8 m
Margin depth settings	Fixed

Display

Display	LCD
---------	-----

Network

Ethernet LAN	Yes
--------------	-----

Memory

Internal memory	256 MB
Flash memory	512 MB

Paper handling

Maximum roll diameter	21.3 cm
Maximum label width	11.4 cm
Core diameter	7.62 cm

Ports & interfaces

USB 2.0 ports quantity	1
RS-232 ports	1
Connectivity technology	Wired
USB port	Yes

Performance

Mobile operating systems supported	Android, iOS
Languages support	Simplified Chinese, Traditional Chinese, German, English, Spanish, French, Italian, Japanese, Korean, Portuguese, Russian, Thai
Built-in barcodes	1D, 2D
Image formats supported	BMP, GIF, PCX, PNG
Page description languages	DP, DPL, IPL, XML, ZPL II

Design

Product colour	Black	Compliance certificates	CE, RoHS
Control type	Touch	System requirements	
Built-in display	Yes	Linux operating systems supported	Yes
Power		Operational conditions	
Power consumption (standby)	9.6 W	Storage temperature (T-T)	-20 - 70 °C
AC input voltage	100 - 240 V	Storage relative humidity (H-H)	5 - 90%
AC input frequency	50 - 60 Hz	Operating temperature (T-T)	5 - 40 °C
Technical details		Operating relative humidity (H-H)	20 - 85%
Windows operating systems supported	Yes	Weight & dimensions	
Supported network protocols	TCP/IP suite (TCP, UDP, ICMP, IGMP), LPR/ LPD, Telnet/SSH, FTP/SFTP, BOOTP, DHCP, HTTP/HTTPS, SNMPv1/2c/3, SNMP-MIBII supported – over UDP/IP (private enterprise MIB included), SMTP Supports IPv4 and IPv6	Width	253 mm
Sustainability certificates	ENERGY STAR	Depth	432 mm
		Height	181 mm
		Weight	12.6 kg

Order or get advice

Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434

website@barcodegenie.co.uk

Scan to view this product online.

