

# Honeywell PM45A

Honeywell PM45A label printer Thermal transfer 300 x 300 DPI 300 mm/sec Wired Ethernet LAN



PRINT TECHNOLOGY

**Thermal transfer**

RESOLUTION

**300 x 300 DPI**

PRINT SPEED

**300 mm/sec**

MAX PRINT WIDTH

**10.6 cm**

MAX LABEL WIDTH

**11.4 cm**

CONNECTIVITY

**USB, Ethernet**

PRINTER LANGUAGES

**DP, DPL, IPL, XML, ZPL II**

## OVERVIEW

PM45A, Full Touch Display, Ethernet, Fixed Hanger, Rewinder + label taken sense, Thermal Transfer, 300 DPI, Power Cord Not Included

## TECHNICAL SPECIFICATIONS

### Print quality

|                        |               |
|------------------------|---------------|
| Maximum resolution     | 300 x 300 DPI |
| Maximum printing width | 10.6 cm       |

### Printing

|                       |                  |
|-----------------------|------------------|
| Colour                | No               |
| Printing colours      | Black            |
| Print speed           | 300 mm/sec       |
| Print technology      | Thermal transfer |
| Margin depth settings | Fixed            |

### Display

|         |     |
|---------|-----|
| Display | LCD |
|---------|-----|

### Network

|              |     |
|--------------|-----|
| Wi-Fi        | No  |
| Ethernet LAN | Yes |

### Memory

|                 |        |
|-----------------|--------|
| Internal memory | 256 MB |
| Flash memory    | 512 MB |

### Paper handling

|                       |         |
|-----------------------|---------|
| Maximum roll diameter | 21.3 cm |
| Maximum label width   | 11.4 cm |
| Core diameter         | 7.62 cm |

### Ports & interfaces

|                         |       |
|-------------------------|-------|
| USB 2.0 ports quantity  | 2     |
| RS-232 ports            | 1     |
| Connectivity technology | Wired |
| USB port                | Yes   |

### Performance

|                                    |                           |
|------------------------------------|---------------------------|
| Mobile operating systems supported | Android, iOS              |
| Built-in barcodes                  | 1D, 2D                    |
| Page description languages         | DP, DPL, IPL, XML, ZPL II |

### Design

|                  |       |
|------------------|-------|
| Product colour   | Black |
| Control type     | Touch |
| Built-in display | Yes   |

### Power

|                             |             |
|-----------------------------|-------------|
| Power consumption (standby) | 9.6 W       |
| AC input voltage            | 100 - 240 V |
| AC input frequency          | 50 - 60 Hz  |

### Technical details

|                                     |             |
|-------------------------------------|-------------|
| Windows operating systems supported | Yes         |
| Sustainability certificates         | ENERGY STAR |
| Compliance certificates             | CE, RoHS    |

### System requirements

|                                   |     |
|-----------------------------------|-----|
| Linux operating systems supported | Yes |
|-----------------------------------|-----|

### Operational conditions

|                                   |             |
|-----------------------------------|-------------|
| Storage temperature (T-T)         | -20 - 70 °C |
| Storage relative humidity (H-H)   | 5 - 90%     |
| Operating temperature (T-T)       | 5 - 40 °C   |
| Operating relative humidity (H-H) | 20 - 85%    |

### Weight & dimensions

|        |        |
|--------|--------|
| Width  | 284 mm |
| Depth  | 483 mm |
| Height | 295 mm |

### Order or get advice

Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

**0113 487 7434**

[website@barcodegenie.co.uk](mailto:website@barcodegenie.co.uk)

Scan to view this product online.

