Honeywell PX45A

Honeywell PX45A label printer Thermal transfer 300 x 300 DPI 300 mm/sec Wired Ethernet LAN



PRINT TECHNOLOGY
Thermal transfer

RESOLUTION
300 x 300 DPI

PRINT SPEED
300 mm/sec

MAX PRINT WIDTH
11 cm

CONNECTIVITY
USB, Ethernet

OVERVIEW

300DPI, 300mm/s, Ethernet, RS232, USB, 256/512 MB, LCD

TECHNICAL SPECIFICATIONS

Print quality

Maximum resolution	300 x 300 DPI
Maximum printing width	11 cm

Printing

Print speed	300 mm/sec
Print technology	Thermal transfer

Display

Display	LCD

Network

Wi-Fi	No
Ethernet LAN	Yes

Memory

Internal memory	256 MB
Flash memory	512 MB

Paper handling

Maximum roll diameter	21.3 cm
Core diameter	7.62 cm

Ports & interfaces

USB 2.0 ports quantity	2
RS-232 ports	1
Connectivity technology	Wired
USB port	Yes

Performance

Built-in barcodes	1D, 2D

Design

Product colour	Black
Built-in display	Yes

Power

Power consumption (standby)	5 W

Operational conditions

Storage temperature (T-T)	-20 - 70 °C
Storage relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	5 - 40 °C
Operating relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	275 mm
Depth	482 mm
Height	238 mm

Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.

Weight	12.6 kg

Order or get advice
Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434
website@barcodegenie.co.uk
Scan to view this product online.

Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.