Honeywell PX65A

Honeywell PX65A label printer Thermal transfer 203 x 203 DPI 225 mm/sec Wired Ethernet LAN



PRINT TECHNOLOGY
Thermal transfer

RESOLUTION
203 x 203 DPI

PRINT SPEED
225 mm/sec

MAX PRINT WIDTH
16.7 cm

CONNECTIVITY
USB, Ethernet

OVERVIEW

203DPI, 225mm/s, Ethernet, RS232, USB, 256/512 MB, LCD

TECHNICAL SPECIFICATIONS

Print quality

Maximum resolution	203 x 203 DPI
Maximum printing width	16.7 cm

Printing

Print speed	225 mm/sec
Print technology	Thermal transfer

Display

Display	LCD

Network

Wi-Fi	No
Ethernet LAN	Yes

Memory

Internal memory	256 MB
Flash memory	512 MB

Paper handling

Maximum roll diameter	21.3 cm
Core diameter	7.62 cm

Ports & interfaces

USB 2.0 ports quantity	2
RS-232 ports	1
Connectivity technology	Wired
Bluetooth	No
USB port	Yes

Performance

Built-in barcodes	1D, 2D

Design

Product colour	Black
Built-in display	Yes

Power

Power consumption (standby)	5 W

Operational conditions

Storage temperature (T-T)	-20 - 70 °C
Storage relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	5 - 40 °C
Operating relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	335 mm
Depth	482 mm
Height	238 mm
Weight	12.6 kg

Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.

Order or get advice
Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434
website@barcodegenie.co.uk
Scan to view this product online.

Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.