

Honeywell PX65A

Honeywell PX65A label printer Thermal transfer 300 x 300 DPI 225 mm/sec Wired Ethernet LAN Wi-Fi



PRINT TECHNOLOGY
Thermal transfer

RESOLUTION
300 x 300 DPI

PRINT SPEED
225 mm/sec

MAX PRINT WIDTH
16.7 cm

MAX LABEL WIDTH
16.7 cm

CONNECTIVITY
USB, Ethernet, Wi-Fi

PRINTER LANGUAGES
DP, DPL, XML, ZPL II, IPL

OVERVIEW

300DPI, 225mm/s, Ethernet, RS232, USB, 256/512 MB, LCD, Wi-fi

TECHNICAL SPECIFICATIONS

Print quality

Maximum resolution	300 x 300 DPI
Maximum printing width	16.7 cm

Printing

Colour	No
Print speed	225 mm/sec
Print technology	Thermal transfer
Printing characters	2D barcode, Barcode, Graphic, Text

Display

Display	LCD
---------	-----

Network

Wi-Fi	Yes
Ethernet LAN	Yes

Memory

Internal memory	256 MB
Flash memory	512 MB

Paper handling

Media thickness	0.061 - 0.254 mm
-----------------	------------------

Maximum roll diameter	21.3 cm
Maximum label width	16.7 cm
Core diameter	7.62 cm

Ports & interfaces

USB 2.0 ports quantity	2
RS-232 ports	1
Connectivity technology	Wired
Bluetooth	No
USB port	Yes

Performance

Built-in barcodes	1D, 2D
Page description languages	DP, DPL, XML, ZPL II, IPL

Design

Product colour	Black
Built-in display	Yes

Power

Power consumption (standby)	5 W
-----------------------------	-----

Operational conditions

Storage temperature (T-T) -20 - 70 °C

Storage relative humidity (H-H) 10 - 90%

Operating temperature (T-T) 5 - 40 °C

Operating relative humidity (H-H) 10 - 90%

Weight & dimensions

Width 335 mm

Depth 482 mm

Height 238 mm

Weight 12.6 kg

Order or get advice

Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434

website@barcodegenie.co.uk

Scan to view this product online.

