Honeywell PX940

Honeywell PX940 label printer Direct thermal / Thermal transfer 203 x 203 DPI Wired & Wireless Ethernet LAN Bluetooth



PRINT TECHNOLOGY
Direct thermal / Thermal transfer

RESOLUTION
203 x 203 DPI

MAX PRINT WIDTH
10.8 cm

CONNECTIVITY
USB, Ethernet, Bluetooth

PRINTER LANGUAGES
DP, DPL, XML, ZPL II, IPL

OVERVIEW

LCD 3.5" Touch, 203 dpi, 1 GB DDR3, 256 MB Flash, 506 x 398.7 x 261 mm

KEY FEATURES

- Extremely precise printing of up to +/-0.2 mm (0.0079 in) virtually eliminates poor-quality, unreadable labels and barcodes.
- Integrated label verification technology checks and ensures that barcodes are accurate every time: instantly notifies you of pass/fail status and ANSI grade.
- Easy to use and maintain, with a color multilingual touchscreen interface and quick side-loading design.
- Smart printing capability allows users to configure and print without the need for a host computer.
- Operational Intelligence software provides predictive analytics and data on printer health to help managers oversee their entire printer fleet and proactively prevent issues, ensuring maximum uptime.

TECHNICAL SPECIFICATIONS

Print quality

Maximum resolution	203 x 203 DPI
Maximum printing width	10.8 cm

Printing

Minimum print length	4.8 m
Colour	No
Print technology	Direct thermal / Thermal transfer

Display

Display diagonal	8.89 cm (3.5")
Display	LCD

Network

Ethernet LAN	Yes

Memory

Internal memory	1024 MB
Flash memory	256 MB

Paper handling

Ribbon width	11 cm
Ribbon length	450 m
Maximum roll diameter	8 cm
Core diameter	2.54 cm

Ports & interfaces

USB 2.0 ports quantity	2
Connectivity technology	Wired & Wireless
Bluetooth	Yes
USB port	Yes
Bluetooth Low Energy (BLE)	Yes

Performance

Built-in processor	Yes

Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.

Page description languages	DP, DPL, XML, ZPL II, IPL

Design

Product colour	Black
Built-in display	Yes

Power

AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz

Operational conditions

Operating temperature (T-T)	5 - 40 °C
Operating relative humidity (H-H)	20 - 85%

Weight & dimensions

Width	261 mm
Depth	506 mm
Height	398.7 mm
Weight	23 kg

Packaging content

Cables included	AC

Order or get advice
Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434
website@barcodegenie.co.uk
Scan to view this product online.

Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.