SATO CL4NX Plus 203 x 203 DPI Wired & Wireless Direct thermal

SATO CL4NX Plus 203 x 203 DPI Wired & Wireless Direct thermal POS printer



PRINT TECHNOLOGY
Direct thermal

RESOLUTION
203 x 203 DPI

PRINT SPEED
14 ips

MAX PRINT WIDTH
10.4 cm

CONNECTIVITY
USB, Ethernet, Bluetooth

OVERVIEW

203 dpi (8 dots/mm), 14 ips (355mm/sec), USB 2.0, Ethernet, RS-232C, Bluetooth, NFC, 3.5" Full Color LCD, UK

KEY FEATURES

- Full color interactive LCD with Intuitive Menu Navigation
- On-board Help Videos
- Tool-less Maintenance
- 10-inch media supply (Face-in/Face-out wind) and 600m ribbon (CSI/CSO) supported
- Multiple Interfaces - Auto Switching
- Competitive Emulations On-board - Auto Switching
- Micro Label Print Mode
- Print speeds up to 14 ips in either 203 or 305 dpi
- HF or UHF RFID support with SATO RF Analyze (SRA) **Coming Fall 2020
- Smart Print Head and Pure Line Platen Roller

TECHNICAL SPECIFICATIONS

Printing

Type	POS printer
Print technology	Direct thermal
Print speed	14 ips
Maximum resolution	203 x 203 DPI

Performance

Built-in barcodes	Code 129-Auto, Code 39, Code 93, GS1-128, Industrial 2/5, MSI, Matrix 2/5, POSTNET, UPC-A, UPC-E

Paper handling

Maximum media length	60 cm
Supported paper width	39.5 - 128 mm
Printing media thickness	0.06 - 0.268 µm
Maximum roll diameter	25.4 cm
Maximum printing width	10.4 cm

Ports & interfaces

Connectivity technology	Wired & Wireless
USB 2.0 ports quantity	3
Bluetooth version	3.0+HS
Bluetooth	Yes
USB port	Yes
USB connector	USB Type-A / USB Type-B

Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.

Serial interface	Yes
Serial interface type	RS-232C

Network

Ethernet LAN	Yes

Technical details

Product colour	Black

Design

Display diagonal	8.89 cm (3.5")
Colour display	Yes
Built-in display	Yes

Power

AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power source type	AC

Operational conditions

Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	30 - 90%
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	30 - 80%

Weight & dimensions

Width	457 mm
Depth	271 mm
Height	321 mm
Weight	15.1 kg

Order or get advice
Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434
website@barcodegenie.co.uk
Scan to view this product online.

Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.