

SATO CT4-LX 203 x 203 DPI Wired & Wireless Direct thermal / Thermal transfer

SATO CT4-LX 203 x 203 DPI Wired & Wireless Direct thermal / Thermal transfer POS printer



PRINT TECHNOLOGY
Direct thermal / Thermal transfer

RESOLUTION
203 x 203 DPI

PRINT SPEED
8 ips

MAX PRINT WIDTH
11.8 cm

CONNECTIVITY
USB, Ethernet

OVERVIEW

203 dpi, 8 ips, Thermal Transfer / Direct Thermal, 4GB Flash, 1GB RAM, USB&LAN, EU/UK

KEY FEATURES

- 4.3" Full Color Touchscreen Display
- 203 or 305 dpi print resolution
- Thermal Transfer and Direct Thermal
- Label Waste Prevention and media profiles
- Auto Switching competitive emulation languages (SBPL, SEPL, SZPL, SDPL, SIPL or STCL)
- Application Enabled Printing (AEP)
- SATO Online Services (SOS) and SOTI Connect supported
- SATO RF Analyze (SRA) for RFID
- PDF Direct Printing

TECHNICAL SPECIFICATIONS

Printing

Type	POS printer
Print technology	Direct thermal / Thermal transfer
Print speed	8 ips
Maximum resolution	203 x 203 DPI

Performance

Built-in barcodes	1D, 2D, Code 128 (A/B/C), Code 39, Code 93, EAN13, EAN8, GS1 DataBar, GS1-128, Industrial 2/5, Interleaved 2/5, Matrix 2/5
-------------------	--

Paper handling

Maximum media length	40 cm
Supported paper width	25 - 118 mm
Printing media thickness	0.08 - 0.19 µm
Maximum roll diameter	12.8 cm
Maximum printing width	11.8 cm

Ports & interfaces

Connectivity technology	Wired & Wireless
USB 2.0 ports quantity	2
USB port	Yes
USB connector	USB Type-A / USB Type-B
Serial interface	No

Near Field Communication (NFC) Yes

Network

Ethernet LAN	Yes
Wi-Fi	No

Technical details

Product colour	Black
----------------	-------

Features

Internal memory	1024 MB
Flash memory	4096 MB
Storage media	Flash
Internal storage capacity	4 GB

Design

Display diagonal	10.9 cm (4.3")
Colour display	Yes
Built-in display	Yes

Power

AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power source type	AC

Operational conditions

Storage temperature (T-T)	-10 - 60 °C
Storage relative humidity (H-H)	15 - 90%
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	30 - 80%

Weight & dimensions

Width	177.8 mm
Depth	238 mm
Height	214.1 mm
Weight	3.4 kg

Order or get advice

Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434

website@barcodegenie.co.uk

Scan to view this product online.

