Star Micronics TSP743II-24

Star Micronics TSP743II-24 label printer Thermal transfer 250 mm/sec



PRINT TECHNOLOGY
Thermal transfer

PRINT SPEED
250 mm/sec

MAX PRINT WIDTH
8.25 cm

OVERVIEW

Thermal, 80mm Wide Paper, 24VDC (Requires PS60 PSU), Cutter, No Interface, Charcoal Grey Case

TECHNICAL SPECIFICATIONS

Print quality

Maximum printing width	8.25 cm

Printing

Colour	No
Print speed	250 mm/sec
Print technology	Thermal transfer

Network

Wi-Fi	No
Ethernet LAN	No

Performance

Certification	UL, C-UL, TÜV, FCC, VCCI, EN55022, CE, Gost

Design

Product colour	Grey

Operational conditions

Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	5 - 45 °C
Operating relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	147 mm
Depth	213 mm
Height	148 mm
Weight	1.75 kg

Order or get advice
Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434
website@barcodegenie.co.uk
Scan to view this product online.

Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.