

Star Micronics TSP743U II

Star Micronics TSP743U II label printer Direct thermal 406 x 203 DPI 250 mm/sec



PRINT TECHNOLOGY
Direct thermal

RESOLUTION
406 x 203 DPI

PRINT SPEED
250 mm/sec

MAX PRINT WIDTH
8 cm

MAX LABEL WIDTH
8.25 cm

CONNECTIVITY
USB

OVERVIEW

TSP743U II - 203 dpi, 250 mm/s, Thermal Printer, USB, W/O PSU

TECHNICAL SPECIFICATIONS

Print quality

Maximum resolution	406 x 203 DPI
Maximum printing width	8 cm

Printing

Colour	No
Print speed	250 mm/sec
Print technology	Direct thermal

Network

Wi-Fi	No
Ethernet LAN	No

Paper handling

Supported paper width	58, 80, 82.5 mm
Media thickness	0.06-0.15 mm
Maximum roll diameter	10 cm
Maximum label width	8.25 cm
Autocutter durability	2 million cuts
Autocutter	Yes

Ports & interfaces

USB 2.0 ports quantity	1
USB port	Yes

Performance

Built-in barcodes	Code 39, Code 93, Code-128 Codabar Library, ITF, UPC-A, UPC-E
Certification	UL, C-UL, TÜV, FCC, VCCI, EN55022, CE, Gost
Cutter	Yes

Design

Product colour	Grey
----------------	------

Power

AC adapter output voltage	24 V
---------------------------	------

Operational conditions

Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	5 - 45 °C
Operating relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	147 mm
Depth	213 mm

Height	148 mm	Weight	1.75 kg
--------	--------	--------	---------

Order or get advice

Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434

website@barcodegenie.co.uk
Scan to view this product online.

