TSC DA210

TSC DA210 label printer Direct thermal 203 x 203 DPI 152.4 mm/sec Wired



PRINT TECHNOLOGY
Direct thermal

RESOLUTION
203 x 203 DPI

PRINT SPEED
152.4 mm/sec

MAX PRINT WIDTH
10.8 cm

CONNECTIVITY
USB

PRINTER LANGUAGES
TSPL-EZ

OVERVIEW

DA210 Desktop Direct Thermal Bar Code Printer, 203 dpi, 152.4 mm/s, 8MB Flash, 16MB DRAM, USB 2.0

KEY FEATURES

- Small Parcel Shipping
- Mail Room Address and Routing Labels
- Shipping & Receiving
- Entertainment and Transportation Ticketing
- Retail Point-of-Sale
- File-Folder Labeling

TECHNICAL SPECIFICATIONS

Print quality

Maximum resolution	203 x 203 DPI
Maximum printing width	10.8 cm

Printing

Rotated printing	Yes
Colour	No
Print speed	152.4 mm/sec
Print technology	Direct thermal

Display

Display	No

Network

Wi-Fi	No
Ethernet LAN	No

Memory

Internal memory	16 MB
Flash memory	8 MB

Paper handling

Supported paper width	19 - 114 mm
Media thickness	0.055 - 0.19 mm
Maximum roll diameter	12.7 cm
Maximum media length	2.79 m

Ports & interfaces

Optional connectivity	Bluetooth
Connectivity technology	Wired
USB port	Yes

Performance

Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.

Built-in barcodes	AZTECCODE, Code 11, Code 128 (A/B/C), Code 39, Code 93, Data Matrix, EAN128, EAN13, EAN8, GS1 DataBar, Interleaved 2/5, MaxiCode, MicroPDF417, PDF417, POSTNET, QR Code, UPC-A, UPC-E
Certification	FCC Class A, CE Class A, RCM, CB, CCC, ENERGY STAR, KC, BIS, UL, EAC
Page description languages	TSPL-EZ

Design

Product colour	Black
Built-in display	No

Power

AC adapter output voltage	24 V
AC adapter output current	2.5 A
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz

Technical details

Windows operating systems supported	Yes
Mac operating systems supported	Yes
Sustainability certificates	ENERGY STAR

System requirements

Linux operating systems supported	Yes

Operational conditions

Storage temperature (T-T)	-40 - 60 °C
Storage relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	5 - 40 °C
Operating relative humidity (H-H)	25 - 85%

Weight & dimensions

Width	172 mm
Depth	195 mm
Height	165 mm
Weight	1.5 kg

Packaging content

Cables included	AC, USB

Order or get advice
Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434
website@barcodegenie.co.uk
Scan to view this product online.

Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.