

TSC MB241T

TSC MB241T label printer Direct thermal / Thermal transfer 203 x 203 DPI 304.8 mm/sec Wired & Wireless Ethernet LAN Wi-Fi Bluetooth



PRINT TECHNOLOGY

Direct thermal / Thermal transfer

RESOLUTION

203 x 203 DPI

PRINT SPEED

304.8 mm/sec

MAX PRINT WIDTH

10.7 cm

CONNECTIVITY

USB, Ethernet, Wi-Fi, Bluetooth

PRINTER LANGUAGES

DPL, EPL, TSPL, TSPL-EZ, ZPL, ZPL II

OVERVIEW

203 dpi, 304.8 mm/s, DRAM 256 MB/Flash 256 MB, USB, Wi-Fi, EU EMEA

TECHNICAL SPECIFICATIONS

Print quality

Maximum resolution	203 x 203 DPI
Maximum printing width	10.7 cm
Maximum print height	2.54 cm

Printing

Colour	No
Print speed	304.8 mm/sec
Print technology	Direct thermal / Thermal transfer

Display

Display diagonal	10.2 cm (4")
Display	LCD

Network

Wi-Fi	Yes
Ethernet LAN	Yes

Memory

Internal memory	256 MB
Flash memory	256 MB

Paper handling

Ribbon width	11 cm
Ribbon length	450 m
Maximum media length	12 cm

Ports & interfaces

Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
RS-232 ports	1
Connectivity technology	Wired & Wireless
Bluetooth	Yes
USB port	Yes

Performance

Built-in barcodes	1D, 2D, AZTECCODE, China post, Code 11, Code 128 (A/B/C), Code 39, Code 93, Code-128 Codabar Library, Code128UCC, Datamatrix, EAN128, EAN13, EAN8, GS1 DataBar, Interleaved 2/5, MSI, MaxiCode, PDF417, POSTNET, Plessey, QR Code, TLC39, UPC-A, UPC-E
Built-in RFID module	Yes
Built-in processor	Yes

Page description languages	DPL, EPL, TSPL, TSPL-EZ, ZPL, ZPL II
Tape end detection	Yes
Open cover detection	Yes
Design	
Product colour	Black
Control type	Touch
Built-in display	Yes
Power	
AC adapter output voltage	24 V
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Technical details	
Warranty period	2 year(s)
Compliance certificates	BIS, BSMI, CB, CCC, CE, EAC, Federal Communications Commission (FCC), Industry Canada (IC), KC, Norma Oficial Mexicana (NOM), RCM, TÜV mark, UKCA, VCCI, cTUVus

Operational conditions

Storage temperature (T-T)	10 - 90 °C
Storage relative humidity (H-H)	-40 - 60%
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	25 - 85%

Weight & dimensions

Width	248 mm
Depth	436 mm
Height	274 mm
Weight	9.1 kg

Packaging content

Cables included	AC, USB
-----------------	---------

Order or get advice

Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434

website@barcodegenie.co.uk

Scan to view this product online.

