TSC MH341T

TSC MH341T label printer Direct thermal / Thermal transfer 300 x 300 DPI 305 mm/sec Wired



PRINT TECHNOLOGY
Direct thermal / Thermal transfer

RESOLUTION
300 x 300 DPI

PRINT SPEED
305 mm/sec

MAX PRINT WIDTH
10.4 cm

CONNECTIVITY
USB

OVERVIEW

300 dpi, LCD, USB, Ethernet, Wi-Fi, 256 MB

TECHNICAL SPECIFICATIONS

Print quality

Maximum resolution	300 x 300 DPI
Maximum printing width	10.4 cm

Printing

Print speed	305 mm/sec
Print technology	Direct thermal / Thermal transfer

Display

Colour display	Yes
Display	LCD

Network

Wi-Fi	No
Ethernet LAN	No

Memory

Internal memory	256 MB
Flash memory	512 MB

Paper handling

Ribbon width	11.4 cm
Ribbon length	600 m
Core diameter	7.62 cm

Ports & interfaces

RS-232 ports	1
Optional connectivity	Bluetooth, Ethernet, Serial (RS-232), Wireless LAN
Connectivity technology	Wired
Bluetooth	No
USB port	Yes

Performance

Number of fonts	8

Design

Product colour	Black
Control type	Buttons
Built-in display	Yes

Operational conditions

Storage temperature (T-T)	-40 - 60 °C
Storage relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	25 - 85%

Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.

Weight & dimensions	
Width	276 mm
Depth	502 mm
Height	326 mm
Weight	15.7 kg

Order or get advice
Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434
website@barcodegenie.co.uk
Scan to view this product online.

Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.