

TSC TE300

TSC TE300 label printer Direct thermal / Thermal transfer 300 x 300 DPI 127 mm/sec Wired



PRINT TECHNOLOGY

Direct thermal / Thermal transfer

RESOLUTION

300 x 300 DPI

PRINT SPEED

127 mm/sec

MAX PRINT WIDTH

10.6 cm

CONNECTIVITY

USB

PRINTER LANGUAGES

EPL, TSPL-EZ, ZPL, ZPL II

OVERVIEW

TSC TE300, TSPL-EZ, USB

TECHNICAL SPECIFICATIONS

Print quality

Maximum resolution	300 x 300 DPI
Maximum printing width	10.6 cm

Printing

Colour	No
Print speed	127 mm/sec
Print technology	Direct thermal / Thermal transfer

Display

Display	No
---------	----

Network

Wi-Fi	No
Ethernet LAN	No

Memory

Internal memory	16 MB
Flash memory	8 MB

Paper handling

Supported paper width	40 - 110 mm
Media thickness	0.06 - 0.19 mm
Maximum roll diameter	3.8 cm

Maximum media length	101.6 cm
----------------------	----------

Ports & interfaces

USB 2.0 ports quantity	1
Connectivity technology	Wired
USB port	Yes

Performance

Built-in barcodes	1D, Code 93, GS1 DataBar, QR Code, AZTECCODE, Interleaved 2/5, UPC-A, CODABAR (NW-7), Data Matrix, UPC-E, Code 11, EAN128, MaxiCode, EAN13, MicroPDF417, Code 39, EAN8, PDF417, Code 49, ITF-14, POSTNET
Number of fonts	8
Built-in processor	Yes
Certification	RoHS, WEEE
Page description languages	EPL, TSPL-EZ, ZPL, ZPL II

Design

Product colour	Black
Built-in display	No

Power

Power consumption (printing)	60 W
AC input voltage	100 - 240 V
AC input frequency	50 Hz

Technical details

Compliance certificates	REACH, RoHS, WEEE
-------------------------	-------------------

Operational conditions

Storage temperature (T-T)	-40 - 60 °C
Storage relative humidity (H-H)	10 - 90%

Operating temperature (T-T)	5 - 40 °C
Operating relative humidity (H-H)	25 - 85%

Weight & dimensions

Width	204 mm
Depth	280 mm
Height	164 mm
Weight	2.4 kg

Packaging content

Cables included	AC, USB
-----------------	---------

Order or get advice

Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434

website@barcodegenie.co.uk
Scan to view this product online.

