

TSC TH240

TSC TH240 label printer Direct thermal / Thermal transfer 203 x 203 DPI 203 mm/sec Wired & Wireless Ethernet LAN Wi-Fi Bluetooth



PRINT TECHNOLOGY
Direct thermal / Thermal transfer

RESOLUTION
203 x 203 DPI

PRINT SPEED
203 mm/sec

MAX PRINT WIDTH
10.8 cm

CONNECTIVITY
USB, Ethernet, Wi-Fi, Bluetooth

PRINTER LANGUAGES
DP, EPL, TSPL, TSPL-EZ, ZPL, ZPL II

OVERVIEW

203 dpi, DRAM 128MB/Flash 128MB, USB, RS-232, Ethernet, USB Host, RTC, Buzzer

TECHNICAL SPECIFICATIONS

Print quality

Maximum resolution	203 x 203 DPI
Maximum printing width	10.8 cm
Maximum print height	2.54 cm

Printing

Colour	No
Print speed	203 mm/sec
Print technology	Direct thermal / Thermal transfer

Display

Display	LED
---------	-----

Network

Wi-Fi	Yes
Ethernet LAN	Yes

Memory

Internal memory	128 MB
Flash memory	128 MB

Paper handling

Ribbon width	11 cm
--------------	-------

Ribbon length	300 m
Maximum media length	12 cm

Ports & interfaces

Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
RS-232 ports	1
Connectivity technology	Wired & Wireless
Bluetooth version	5.0
Bluetooth	Yes
USB port	Yes

Performance

Built-in barcodes	1D, 2D, AZTECCODE, China post, Codablock F, Code 11, Code 128 (A/B/C), Code 39, Code 49, Code 93, Code-128 Codabar Library, Code128UCC, Deutsche Post Identcode, Deutsche Post Leitcode, EAN128, EAN13, EAN14, EAN8, GS1 DataBar, ITF-14, Interleaved 2/5, LOGMARS, MSI, MaxiCode, MicroPDF417, PDF417, Planet, POSTNET, Plessey, QR Code, TELEPEN, TELEPENN, TLC39, UPC-A, UPC-E
-------------------	---

Built-in processor	Yes
Page description languages	DP, EPL, TSPL, TSPL-EZ, ZPL, ZPL II
Tape end detection	Yes
Open cover detection	Yes

Design

Product colour	Black
Control type	Buttons
Built-in display	Yes

Power

AC adapter output voltage	24 V
AC adapter output current	3.75 A
Power consumption (printing)	90 W
AC input voltage	100 - 240 V

AC input frequency	50 - 60 Hz
--------------------	------------

Technical details

Sustainability certificates	ENERGY STAR
Warranty period	2 year(s)
Compliance certificates	BIS, BSMI, CB, CCC, CE, EAC, Federal Communications Commission (FCC), Industry Canada (IC), KC, Norma Oficial Mexicana (NOM), UKCA, cTUVus

Operational conditions

Storage temperature (T-T)	10 - 90 °C
Storage relative humidity (H-H)	25 - 85%
Operating temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	0 - 45%

Weight & dimensions

Width	223 mm
Depth	286 mm
Height	186 mm
Weight	2.8 kg

Packaging content

Cables included	AC, USB
-----------------	---------

Order or get advice

Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434

website@barcodegenie.co.uk

Scan to view this product online.

