

TSC TX210

TSC TX210 label printer Direct thermal / Thermal transfer 203 x 203 DPI 203 mm/sec Wired & Wireless Ethernet LAN Wi-Fi Bluetooth



PRINT TECHNOLOGY

Direct thermal / Thermal transfer

RESOLUTION

203 x 203 DPI

PRINT SPEED

203 mm/sec

MAX PRINT WIDTH

10.8 cm

CONNECTIVITY

USB, Ethernet, Wi-Fi, Bluetooth

PRINTER LANGUAGES

DPL, EPL, TSPL-EZ, ZPL, ZPL II

OVERVIEW

Printer TX210 WiFi Ready, 8 dots/mm (203 dpi), TSPL-EZ, USB, USB Host, RS232, Ethernet

TECHNICAL SPECIFICATIONS

Print quality

Maximum resolution	203 x 203 DPI
Maximum printing width	10.8 cm

Printing

Print speed	203 mm/sec
Print technology	Direct thermal / Thermal transfer

Display

Display	LED
---------	-----

Network

Wi-Fi	Yes
Ethernet LAN	Yes

Memory

Internal memory	128 MB
Flash memory	128 MB

Paper handling

Supported paper width	19 - 112 mm
Ribbon width	11 cm
Ribbon length	300 m

Media thickness	0.055 - 0.254 mm
Maximum roll diameter	12.7 cm
Maximum label length	25.4 m

Ports & interfaces

Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
RS-232 ports	1
Connectivity technology	Wired & Wireless
Bluetooth version	5.0
Bluetooth	Yes
USB port	Yes

Performance

Built-in barcodes	1D, 2D, AZTECCODE, CODABAR (NW-7), China post, Codablock F, Code 11, Code 128 (A/B/C), Code 39, Code 49, Code 93, Code128UCC, Datamatrix, Deutsche Post Identcode, Deutsche Post Leitcode, EAN128, EAN13, EAN14, EAN8, GS1 DataBar, ITF-14, Interleaved 2/5, LOGMARS, MSI, MaxiCode, MicroPDF417, PDF417, Planet, POSTNET, Plessey, QR Code, TELEPEN, TELEPENN, TLC39, UPC-A, UPC-E
-------------------	---

Built-in processor	Yes
Page description languages	DPL, EPL, TSPL-EZ, ZPL, ZPL II
Tape end detection	Yes
Open cover detection	Yes

Design

Product colour	Black
Control type	Buttons
Built-in display	Yes

Power

AC adapter output voltage	24 V
AC adapter output current	3.75 A
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz

Technical details

Sustainability certificates	ENERGY STAR
Warranty period	2 year(s)
Compliance certificates	BIS, CCC, CE, EAC, Federal Communications Commission (FCC), RCM, RoHS, TÜV mark, UL, WEEE, cUL

Software

Bundled software	Windows labeling software CD
------------------	------------------------------

Operational conditions

Storage temperature (T-T)	-40 - 60 °C
Storage relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	5 - 40 °C
Operating relative humidity (H-H)	25 - 85%

Weight & dimensions

Width	226 mm
Depth	332 mm
Height	198 mm
Weight	3.75 kg

Packaging content

Cables included	AC, USB
-----------------	---------

Order or get advice

Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434

website@barcodegenie.co.uk

Scan to view this product online.

