

Zebra ZD220

Zebra ZD220 label printer Direct thermal 203 x 203 DPI 102 mm/sec Wired



PRINT TECHNOLOGY

Direct thermal

RESOLUTION

203 x 203 DPI

PRINT SPEED

102 mm/sec

MAX PRINT WIDTH

10.4 cm

MAX LABEL WIDTH

10.4 cm

CONNECTIVITY

USB

PRINTER LANGUAGES

EPL, EPL2, XML, ZPL, ZPL II

OVERVIEW

203DPI, 8dots, 256MB ROM, 128MB RAM, 220x176x151mm, H, 1.1Kg

TECHNICAL SPECIFICATIONS

Print quality

Maximum resolution	203 x 203 DPI
Maximum printing width	10.4 cm

Printing

Colour	No
Print speed	102 mm/sec
Print technology	Direct thermal

Design

LED indicators	Status
Display	No
Product colour	Black
Built-in display	No
Certification	IEC 60950-1, EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, FCC Class B, ICES-003, FCC 15.209; 15.247(d), IC RSS 247, EN 300 328, EN 301 893, EN 62311, cTUVus CE Marking, VCCI, C-Tick, S-Mark, CCC, CU, BSMI, KCC, SABS, IN-Metro, BIS, NOM

Memory

Internal memory	128 MB
-----------------	--------

Flash memory	256 MB
--------------	--------

Paper handling

Ribbon width	10.9 cm
Ribbon length	74 m
Media thickness	0.08 mm
Maximum roll diameter	12.7 cm
Maximum label width	10.4 cm
Maximum label length	0.991 m

Ports & interfaces

USB 2.0 ports quantity	1
Connectivity technology	Wired
Bluetooth	No
USB port	Yes

Performance

Built-in barcodes	CODABAR (NW-7), Code 11, Code 49, Code 93, Code-128 Codabar Library, Code-39 Library, Data Matrix, EAN13, EAN8, MaxiCode, PDF417, UPC-A, UPC-E
Number of fonts	16

Page description languages	EPL, EPL2, XML, ZPL, ZPL II	Storage temperature (T-T)	-40 - 60 °C
Power		Storage relative humidity (H-H)	5 - 95%
Power plug type	Type C	Operating temperature (T-T)	4.4 - 41 °C
Suitable for use in country/location	Europe, United Kingdom	Operating relative humidity (H-H)	10 - 90%
AC input voltage	100 - 240 V	Weight & dimensions	
AC input frequency	50 - 60 Hz	Width	176 mm
Technical details		Depth	220 mm
Media types supported	Roll-fed, fan-fold, die cut, continuous with or without black mark, tag stock, continuous receipt paper, wristbands	Height	151 mm
Sustainability certificates	ENERGY STAR	Weight	1.1 kg
Operational conditions		Packaging content	
		AC adapter included	Yes
		Cables included	AC

Order or get advice

Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434

website@barcodegenie.co.uk
Scan to view this product online.

