

Zebra ZD230

Zebra ZD230 label printer Thermal transfer 203 x 203 DPI 152 mm/sec Wired



PRINT TECHNOLOGY
Thermal transfer

RESOLUTION
203 x 203 DPI

PRINT SPEED
152 mm/sec

MAX PRINT WIDTH
10.4 cm

MAX LABEL WIDTH
11.2 cm

CONNECTIVITY
USB

PRINTER LANGUAGES
EZPL, XML, ZPL II

OVERVIEW

Thermal Transfer, 203 dpi, 152 mm/s, 104 mm, USB, 1D/2D Bar Codes, EU/UK Power Cords, 1.1 kg

KEY FEATURES

- Thermal Transfer or Direct Thermal print method
- ZPL and EPL programming languages
- Single LED status indicator
- Single button for feed/pause
- USB connectivity
- OpenACCESS™ for easy media loading
- Dual-wall frame construction
- ENERGY STAR qualified

TECHNICAL SPECIFICATIONS

Print quality

Maximum resolution	203 x 203 DPI
Maximum printing width	10.4 cm

Printing

Colour	No
Print speed	152 mm/sec
Print technology	Thermal transfer

Display

Display	No
---------	----

Network

Wi-Fi	No
Ethernet LAN	No

Memory

Internal memory	128 MB
Flash memory	256 MB

Paper handling

Supported paper width	25.4 - 112 mm
Ribbon width	10.9 cm
Ribbon length	300 m
Media thickness	0.08 - 0.1905 mm
Maximum roll diameter	12.7 cm
Maximum label width	11.2 cm
Maximum label length	0.991 m
Core diameter	1.27 cm

Ports & interfaces

USB 2.0 ports quantity	1
Connectivity technology	Wired
Bluetooth	No
USB port	Yes

Performance

Built-in barcodes	1D, 2D, AZTECCODE, CODABAR (NW-7), Code 11, Code 128 (A/B/C), Code 39, Code 49, Code 93, Data Matrix, EAN13, EAN8, Industrial 2/5, Interleaved 2/5, MaxiCode, PDF417, POSTNET, QR Code, UPC-A, UPC-E
Number of fonts	23
Certification	IEC 60950-1, EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, FCC Class B, ICES-003, FCC 15.209; 15.247(d), IC RSS 247, EN 300 328, EN 301 893, EN 62311, cTUVus, CE Marking, VCCI, C-Tick, S-Mark, CCC, CU, BSMI, KCC, SABS, IN-Metro, BIS, NOM
Page description languages	EZPL, XML, ZPL II

Design

Product colour	Black
Built-in display	No

Power

AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz

Operational conditions

Storage temperature (T-T)	-40 - 60 °C
Storage relative humidity (H-H)	5 - 95%
Operating temperature (T-T)	4.4 - 41 °C
Operating relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	197 mm
Depth	267 mm
Height	191 mm
Weight	1.1 kg

Packaging content

Cables included	AC
-----------------	----

Order or get advice

Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434

website@barcodegenie.co.uk

Scan to view this product online.

