

Zebra ZD230

Zebra ZD230 label printer Direct thermal 203 x 203 DPI 152 mm/sec Wired Ethernet LAN



PRINT TECHNOLOGY

Direct thermal

RESOLUTION

203 x 203 DPI

PRINT SPEED

152 mm/sec

MAX PRINT WIDTH

10.4 cm

MAX LABEL WIDTH

11.2 cm

CONNECTIVITY

USB, Ethernet

PRINTER LANGUAGES

EZPL, XML, ZPL II

OVERVIEW

Direct Thermal, 203 dpi, 152 mm/s, 104 mm, USB, 1D/2D Bar Codes, EU/UK Power Cords, Dispenser, 1.1 kg

KEY FEATURES

- Thermal Transfer or Direct Thermal print method
- ZPL and EPL programming languages
- Single LED status indicator
- Single button for feed/pause
- USB connectivity
- OpenACCESS™ for easy media loading
- Dual-wall frame construction
- ENERGY STAR qualified

TECHNICAL SPECIFICATIONS

Print quality

Maximum resolution	203 x 203 DPI
Maximum printing width	10.4 cm

Printing

Colour	No
Print speed	152 mm/sec
Print technology	Direct thermal

Display

Display	No
---------	----

Network

Wi-Fi	No
Ethernet LAN	Yes

Memory

Internal memory	128 MB
Flash memory	256 MB

Paper handling

Supported paper width	25.4 - 112 mm
Ribbon width	10.9 cm
Ribbon length	300 m
Media thickness	0.08 - 0.1905 mm
Maximum roll diameter	12.7 cm
Maximum label width	11.2 cm
Maximum label length	0.991 m
Core diameter	1.27 cm

Ports & interfaces

USB 2.0 ports quantity	1	Built-in display	No
Connectivity technology	Wired	Power	
Bluetooth	No	AC input voltage	100 - 240 V
USB port	Yes	AC input frequency	50 - 60 Hz
Performance		Technical details	
Built-in barcodes	1D, 2D, AZTECCODE, CODABAR (NW-7), Code 11, Code 128 (A/B/C), Code 39, Code 49, Data Matrix, EAN13, EAN8, Industrial 2/5, Interleaved 2/5, MaxiCode, PDF417, POSTNET, QR Code, UPC-A, UPC-E	Sustainability certificates	ENERGY STAR
Number of fonts	23	Operational conditions	
Certification	IEC 60950-1, EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, FCC Class B, ICES-003, FCC 15.209; 15.247(d), IC RSS 247, EN 300 328, EN 301 893, EN 62311, cTUVus, CE Marking, VCCI, C-Tick, S-Mark, CCC, CU, BSMI, KCC, SABS, IN-Metro, BIS, NOM	Storage temperature (T-T)	-40 - 60 °C
Page description languages	EZPL, XML, ZPL II	Storage relative humidity (H-H)	5 - 95%
Design		Operating temperature (T-T)	4.4 - 41 °C
Product colour	Black	Operating relative humidity (H-H)	10 - 90%
		Weight & dimensions	
		Width	176 mm
		Depth	220 mm
		Height	151 mm
		Weight	1.1 kg
		Packaging content	
		Cables included	AC

Order or get advice

Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434

website@barcodegenie.co.uk

Scan to view this product online.

