Zebra ZQ630 Plus

Zebra ZQ630 Plus label printer Direct thermal 203 x 203 DPI 115 mm/sec Wired & Wireless Wi-Fi Bluetooth



PRINT TECHNOLOGY
Direct thermal

RESOLUTION
203 x 203 DPI

PRINT SPEED
115 mm/sec

MAX PRINT WIDTH
10.4 cm

MAX LABEL WIDTH
10.4 cm

CONNECTIVITY
USB, Wi-Fi, Bluetooth

PRINTER LANGUAGES
CPCL-native, EPL, ZBI, ZPL

OVERVIEW

ZQ630 Plus Mobile Printer - Wi-Fi 6, Bluetooth 5, Linered, Shoulder Strap

TECHNICAL SPECIFICATIONS

Print quality

Vertical printing	Yes
Maximum resolution	203 x 203 DPI
Maximum printing width	10.4 cm

Printing

Minimum print length	1.27 cm
Colour	No
Print speed	115 mm/sec
Print technology	Direct thermal

Display

Colour display	Yes
Display resolution	288 x 240 pixels
Display	LCD

Network

Wi-Fi	Yes

Memory

Internal memory	256 MB
Flash memory	512 MB

Paper handling

Media thickness	2.3, 5.5, 6.5 mm
Maximum roll diameter	6.6 cm
Maximum label width	10.4 cm

Ports & interfaces

Wi-Fi standards	Wi-Fi 6 (802.11ax)
Connectivity technology	Wired & Wireless
Bluetooth version	5.3
Bluetooth	Yes
USB port	Yes

Performance

Built-in barcodes	2D, AZTECCODE, CODABAR (NW-7), Code 128 (A/B/C), Code 93, Data Matrix, EAN128, EAN13, EAN8, GS1 DataBar, Interleaved 2/5, MaxiCode, Micro QR Code, MicroPDF417, PDF417, QR Code, TLC39, UPC-A, UPC-E
Number of fonts	26

Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.

Security algorithms	802.1x RADIUS, AES, EAP-FAST, EAP-TLS, EAP-TTLS, LEAP, PEAP, TKIP, WEP, WPA, WPA2
Built-in processor	Yes
Certification	FCC Part 15, Subpart B, EN55022 Class-B, EN60950, EN55024 and VCCI class B, EN55024, EN61000-4-2, EN61000-4-3, EN61000-4-4, and EN61000-4-5, CE, TUV, CSA, Made for iPod/iPhone/iPad
Page description languages	CPCL-native, EPL, ZBI, ZPL

Design

Product colour	Black
Built-in display	Yes

Power

Number of batteries supported	1
Battery type	Built-in battery
Battery technology	Lithium-Ion (Li-Ion)
Battery capacity	6600 mAh

Operational conditions

Storage temperature (T-T)	-25 - 65 °C
Storage relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	0 - 50 °C
Operating relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	165.1 mm
Depth	186.7 mm
Height	82.5 mm
Weight	1.1 kg

Order or get advice
Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

0113 487 7434
website@barcodegenie.co.uk
Scan to view this product online.

Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.