# Zebra ZT411 203 x 203 DPI Wired & Wireless Direct thermal / Thermal transfer

Zebra ZT411 203 x 203 DPI Wired & Wireless Direct thermal / Thermal transfer POS printer



PRINT TECHNOLOGY
**Direct thermal / Thermal transfer**

RESOLUTION
**203 x 203 DPI**

PRINT SPEED
**2.4 ips**

MAX PRINT WIDTH
**10.4 cm**

CONNECTIVITY
**USB, Ethernet, Bluetooth**

## OVERVIEW

203 dpi, 4.3 Display, ARM Cortex A7, 256 MB RAM, 512 MB Flash, USB 2.0, RS-232, Ethernet, Bluetooth 4.1

## TECHNICAL SPECIFICATIONS

### Printing

| | |
|---|---|
| Type | POS printer |
| Print technology | Direct thermal / Thermal transfer |
| Print speed | 2.4 ips |
| Maximum resolution | 203 x 203 DPI |

### Paper handling

| | |
|---|---|
| Maximum media length | 450 m |
| Printing media thickness | 0.058 - 0.25 µm |
| Maximum printing width | 10.4 cm |

### Ports & interfaces

| | |
|---|---|
| Standard interfaces | Bluetooth, Ethernet, RJ-45, RS-232 |
| Connectivity technology | Wired & Wireless |
| USB 2.0 ports quantity | 1 |
| Serial ports quantity | 1 |
| Ethernet LAN (RJ-45) ports | 1 |
| Bluetooth version | 4.1 |
| Bluetooth | Yes |
| USB port | Yes |
| Serial interface | Yes |
| Serial interface type | RS-232 |

### Network

| | |
|---|---|
| Ethernet LAN | Yes |
| Ethernet LAN data rates | 10,100 Mbit/s |

### Technical details

| | |
|---|---|
| Storage media type | Flash |
| Windows operating systems supported | Yes |
| Product colour | Black, Grey |
| Sustainability certificates | ENERGY STAR |

### Features

| | |
|---|---|
| RAM capacity | 256 GB |
| Flash memory | 512 MB |
| Storage media | Flash |

### Design

| | |
|---|---|
| Display diagonal | 10.9 cm (4.3") |
| Colour display | Yes |
| Built-in display | Yes |

### Power


Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.

| | |
|---|---|
| AC input voltage | 100 - 240 V |
| AC input frequency | 50 - 60 Hz |
| Power source type | AC |

### Operational conditions

| | |
|---|---|
| Storage temperature (T-T) | -40 - 60 °C |
| Storage relative humidity (H-H) | 5 - 85% |
| Operating temperature (T-T) | 0 - 40 °C |
| Operating relative humidity (H-H) | 20 - 85% |

### Weight & dimensions

| | |
|---|---|
| Width | 269 mm |
| Depth | 495 mm |
| Height | 324 mm |
| Package weight | 18.6 kg |
| Weight | 16.3 kg |

### Packaging content

| | |
|---|---|
| Quick start guide | Yes |
| AC adapter included | Yes |

**Order or get advice**
Speak to the BarcodeGenie team about compatible labels, ribbons and setup.

**0113 487 7434**
website@barcodegenie.co.uk
Scan to view this product online.


Specifications are supplied by the manufacturer and may change without notice. Issued October 2026.